

# CORDUROY VELVET

- **Composition:**  
100% PES
- **Weight:**  
380 g/m<sup>2</sup>
- **Width:**  
142 cm +/- 2cm
- **Abrasion Resistance:**  
35 000
- **Pilling resistance:**  
5
- **Colour fastness to light:**  
4-5
- **Flammability :**  
BS EN 1021-1:2014  
BS EN 1021-2:2014

- **Usage:**



- **Care guidelines:**



Tullynanegish  
Castleblayney  
Co. Monaghan  
A75 KR58

Tel: 042 9717 943

Mobile: 087 7019 449

Website:

[www.edgartextiles.com](http://www.edgartextiles.com)

Email:

[info@edgartextiles.com](mailto:info@edgartextiles.com)

1. The level of Easy Clean protection can decrease after each cleaning of the fabric, but the process does not affect the look.
2. Respective fabric batches may differ slightly in shade from the colours presented in the sampler.
3. Edgar Textiles is not liable for mechanical damage and such as may be attributable to the improper use and/or cleaning of the fabric.
4. Pilling is caused by the properties of the fabric and is impossible to avoid entirely. This is a natural process, which occurs as the fabric is used.
5. Due to friction against the fabric, colourants can migrate from darker to brighter fabrics.
6. Long-term exposure to sunlight can cause discolouration.
7. FR test performed on foam supplied by the laboratory - RX36110 Combustion modified foam density 34-26kg/m<sup>3</sup>.